

**AMENDMENTS TO THE CLAIMS:**

Insert the following subtitle on page 1 after the title of the invention:  
“TECHNICAL FIELD OF INVENTION”.

Insert the following subtitle on page 1 after the first paragraph:  
“BRIEF DISCUSSION OF RELATED ART”.

Insert the following subtitle before the last paragraph on page 2:  
“BRIEF SUMMARY OF THE INVENTION”.

Insert the following subtitle before the first complete paragraph on page 4:  
“BRIEF DESCRIPTION OF THE DRAWINGS”.

Insert the following subtitle before the third complete paragraph on page 4:  
“DETAILED DESCRIPTION OF THE INVENTION”.

## AMENDMENTS TO THE CLAIMS

Replace the claims with the following listing:

1. (Currently Amended) A door comprising:
  - two lateral posts each having a slideway-(9) bounded by two wings-(8),
  - a transverse element connecting the upper ends of the lateral posts,
  - a flexible curtain-(5) having lateral edges engaging in each of the slideways-(9), and
    - means for winding the curtain-(5) into a door-opening position, characterized in thatwherein each of the slideways-(9) is equipped with a sealing profile-(7) having a back wall-(10) and two lateral walls-(11) substantially forming a U-shape, each of the lateral walls-(11) bearing against the wing-(8) which is adjacent to it.
2. (Currently Amended) The door as claimed in claim 1, characterized in thatwherein each of the lateral walls-(11) is provided with at least one lip-(12) which is able to come into contact with a lateral edge of the curtain-(5).
3. (Currently Amended) The door as claimed in claim 1 or claim 2, characterized in thatwherein each lateral wall-(11) of the sealing profile-(7) is dimensioned such that it bears against the wing-(8) of the slideway-(9) which is adjacent to it.
4. (Currently Amended) The door as claimed in one of claims 1 to 3, characterized in thatwherein the curtain-(5) has a continuous lateral edge-(14) flattened by high-frequency welding.
5. (Currently Amended) The door as claimed in one of claims 1 to 4, characterized in thatwherein each of the lateral walls-(11) and each lip-(12) are tapered at their ends.
6. (Currently Amended) The door as claimed in one of claims 1 to 5, characterized in that, wherein in the a region of the upper end of each post, a guide head-(15) has a U-shaped cross section comprising a back wall-(17) and two lateral walls-(18), each lateral

wall-(18) being provided with a guide rib-(19), the guide head-(15) being positioned in  
the-a continuation of each sealing profile-(7).